

LED 背光源参数表

型号	外形尺寸			发光面面积		正向压降 V _F (V) 在I _F 值下	工作电流 I _F (mA)	发光 颜色	发光 波长 (nm)	发光 亮度 Cd/m ²
	长(L)	宽(W)	高(H)	长(Lv)	宽(Wv)					
JHB1248	48.0	12.4	4.75	46.0	10.4	11.5	40×2	YG	570	180
JHB1551	51.0	15.0	4.7	48.5	12.5	4.6	80	YG	570	180
JHB1685	85.0	16.0	6.0	82	13	4.6	1.4	YG	570	200
JHB1770	70.0	17.0	5.0	66	14	4.6	110	YG	570	200
JHB1854	54.0	18.0	5.0	50	15	4.6	80	YG	570	80
JHB1870	70.0	18.0	4.4	66	14	4.6	110	YG	570	185
JHB1884	84.0	18.2	5.0	82	15	4.6	220	YG	570	200
JHB18125	125.0	17.8	5.3	122	14.8	4.6	200	YG	570	200
JHB1968	68.1	19.0	4.2	65.5	16.5	4.6	140	YG	570	200
JHB2039	39.0	20.0	4.0	34	13	4.6	70	YG	570	180
JHB2068	67.5	20.0	4.0	65	17.5	4.6	110	YG	570	185
JHB20100	100.0	19.5	6.0	90.0	17.3	4.6	150	YG	570	190
JHB2067	67.0	20.4	4.0	64	17.5	4.6	110	YG	570	200
JHB2140	40.0	21.0	4.75	38.0	16.5	4.6	80	YG	570	190
JHB2142	42.0	21.0	5.1	38	17	4.6	80	YG	570	190
JHB2166	65.8	20.6	3.9	62.5	17.3	4.6	100	YG	570	200
JHB2180	80.0	21.0	4.9	76.0	18.0	4.6	180	YG	570	200
JHB21158	158.0	21.0	4.3	159.0	17.0	4.6	360	YG	570	200
JHB2162	61.7	21.0	4.0	58.2	18.0	4.6	100	YG	570	200
JHB2250	50.0	22.0	5.5	46.8	18.8	4.6	100	YG	570	200
JHB2252	52	22	5.8	48	18	4.6	80	YG	570	200
JHB2254	54.0	21.8	3.7	54	18	4.6	80	YG	570	200
JHB2258	58.0	22.0	12	54	18	4.6	90	YG	570	200
JHB2270	70.0	22.0	6.5	66	18	4.6	1110	YG	570	200
JHB2295	95.0	22.0	4.5	90	18	4.6	150	YG	570	200
JHB22100	100.0	22.3	5.4	96	18	4.6	150	YG	570	200
JHB2368	67.8	22.7	6.1	63.9	18.8	4.6	110	YG	570	200
JHB2452	52.0	24.0	3.5	48	20	7.5	80	YG	570	200
JHB2454	54.0	24.0	5.9	51.0	21.0	7.5	80	YG	570	200
JHB2461	61.0	24.0	6.8	58.0	20.0	7.5	90	YG	570	200
JHB2467	66.8	24.0	5.0	63	21	7.5	100	YG	570	200
JHB2468	68.0	23.5	10.0	64.0	19.5	7.5	110	YG	570	200
JHB2485	85.0	24.0	4.5	84	20	7.5	140	YG	570	200
JHB2489	88.9	24.0	4.5	84	20	7.5	150	YG	570	200
JHB24104	104.0	24.0	4.5	100	20	7.5	150	YG	570	200
JHB24160	159.6	23.8	6.3	157	20	4.6	110	YG	570	200
JHB2562	62.0	25.0	4.1	59	22	7.5	90	YG	570	200
JHB2569	69.0	25.0	5.6	65	22	7.5	110	YG	570	200
JHB2575	75.0	25.0	13.0	71	22	7.5	70	YG	570	180

JHB2579	79.0	25.0	4.5	75	22	7.5	120	YG	570	200
JHB2589	89.0	25.0	6.0	85	22	7.5	150	YG	570	180
JHB25110	110.0	25.0	8.0	96	22	7.5	50	YG	570	200
JHB2632	32.0	26.0	5.0	29.5	22.8	7.5	130	YG	570	
JHB2669	68.8	25.5	4.9	66.0	22.5	7.5	130	YG	570	185
JHB2689	89.0	26.0	6.0	85	23	7.5	150	YG	570	200
JHB2691	91.0	26.0	4.5	87	23	7.5	190	YG	570	200
JHB2798	98.5	27.0	7.0	94.5	23.0	7.5	110	YG	570	200
JHB27129	129.0	27.0	5.0	125	23	7.5	130	YG	570	
JHB2868	68.0	28.0	6.1	64	24	7.5	230	YG	570	185
JHB2890	90.0	28.0	12.5	86	24	7.5	100	YG	570	190
JHB28155	155.0	28.0	6.2	151	24	7.5	140	YG	570	200
JHB2966	66.0	29.0	4.2	62	25	7.5	150	YG	570	190
JHB2994	94.0	29	8.4	90	25.0	7.5	230	YG	570	190
JHB29104	103.8	28.8	4.35	100.0	25.0	7.5	120	YG	570	200
JHB29105	104.8	28.9	5.2	99.6	24.5	7.5	150	YG	570	200
JHB29106	106.3	29.0	5.0	102.2	26.0	7.5	120	YG	570	200
JHB29160	160.0	28.5	5.0	156	25	7.5	150	YG	570	200
JHB3080	80.0	29.8	13.0	76	27	7.5	150	YG	570	200
JHB3082	82.0	29.5	5.0	78	27	7.5	140	YG	570	200
JHB3099	99.5	30.0	7.0	95.5	26.0	7.5	150	YG	570	200
JHB30104	104	29.5	5.0	100	27	7.5	110	YG	570	200
JHB3175	75.0	31.0	7.6	71	28	7.5	190	YG	570	200
JHB31109	109.0	30.85	5.2	104.75	27.55	7.5	170	YG	570	200
JHB31114	114.0	31.4	5.4	100	28.4	7.5	210	YG	570	200
JHB31127	127.0	30.5	4.0	123	28	7.5	100	YG	570	200
JHB31114	114.0	31.4	5.4	100	28.4	7.5	210	YG	570	200
JHB3266	66.0	32.0	2.2	62	28	7.5	110	YG	570	200
JHB32144	144.0	32.0	6.2	140	28	7.5	130	YG	570	200
JHB3369	69.0	33.2	5.4	65.0	29.0	7.5	250	YG	570	200
JHB3371	71.0	33.2	4.0	67	29	7.5	110	YG	570	200
JHB3385	85.0	33.2	5.8	81	29	7.5	230	YG	570	200
JHB34154	154.0	34.4	5.5	150	30	7.5	250	YG	570	200
JHB35166	166.0	35.0	68.0	132	31	9.0	120	YG	570	200
JHB35167	167.0	35.3	5.0	163	31.3	9.0	130	YG	570	200
JHB3674	74.0	35.5	4.0	70	31.3	9.0	200	YG	570	200
JHB3686	86.0	36.0	5.0	82	34	9.0	170	YG	570	200
JHB36135	135.0	36.0	8.4	131	32	9.0	200	YG	570	200
JHB37117	117.0	37.0	7.0	114	33	9.0	130	YG	570	200
JHB37135	135.0	37.0	6.6	131	32	9.0	170	YG	570	180
JHB3858	57.6	38.0	5.5	34.5	35	11.5	140	YG	570	200
JHB3887	87.0	37.6	6.6	83	33.6	9.0	85	YG	570	180
JHB38111	111.0	38.0	6.0	109	36	11.5	120	YG	570	200
JHB4080	80.0	40.0	2.2	76	36	11.5	180	YG	570	

JHB4096	96.0	40.0	6.0	91.5	36.0	11.5	140	YG	570	185
JHB40122	122.0	40.4	6.3	116	34.4	11.5	120	YG	570	200
JHB4194	94.0	14.0	5.0	90	37	11.5	210	YG	570	200
JHB4375	75.0	43.0	6.3	71	40	11.5	120	YG	570	200
JHB43142	141.7	43.0	6.7	139	39.5	11.5	120	YG	570	
JHB4474	74.0	44.0	4.6	70	40	11.5	120	YG	570	185
JHB4477	76.5	43.6	4.0	72.5	40	11.5	210	YG	570	190
JHB4478	78.0	44.0	4.2	72.8	40.5	11.5	210	YG	570	200
JHB44140	140.0	44.0	5.0	136	40	11.5	100	YG	570	190
JHB46140	140.0	45.7	5	135.8	41.5	11.5	90	YG	570	190
JHB4967	66.5	49.0	5.7	64.5	45	11.5	200	YG	570	200
JHB5061	61.0	49.5	6.0	57	45.5	11.5	140	YG	570	200
JHB50150	150.0	50.0	64.0	145	45.4	11.5	140	YG	570	200
JHB5198	98.0	51.0	4.9	84	44.9	11.5	140	YG	570	200
JHB51105	105.0	51.0	5.6	101	47	7.5	140	YG	570	200
JHB5498	97.6	53.8	5.2	94	50	150		YG	570	200
JHB62103	103.0	62	6.3	99	58	7.5	140	YG	570	200
JHB65106	106.0	65.0	7.5	103	62	7.5	140	YG	570	200
JHB85110	110.0	84.6	5.0	106	81	7.5	140	YG	570	200
JHB2037	37.0	20.0	4.9	35	18	4.6	80	YG	570	200
JHB2483	83.0	24.0	8.0	80	20.5	4.6	85	YG	570	200
JHB2164	63.5	21.5	5.0	60	66.8	4.6	100	YG	570	200
JHB22104	104.0	22.0	5.4	99.8	17.8	4.6	140	YG	570	200

LED 侧光源参数表

型号	外形尺寸			发光面面积		正向压降 $V_F(V)$ 在 I_F 值下	工作电流 $I_F(mA)$	发光 颜色	发光 波长 (nm)	发光 亮度 Cd/m^2
	长(L)	宽(W)	高(H)	长(L)	宽(WL)					
JHB3552	52.0	35.0	2.2	52	31	2.2/6.6	30/10	YG	570	50
JHB3990	90.0	39	3.3	90	35	4.2	140	YG	570	120
JHB4794	94.0	47.0	3.8	94	43	4.2	140	YG	570	120
JHB2065	65.0	20.0	3.3	62	20	4.2	20	YG	570	20
JHB70124	124.0	70.0	3.6	124	66	4.2	200	YG	570	220